

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : 60-068552

(43)Date of publication of application : 19.04.1985

(51)Int.Cl.

H01M 2/30

(21)Application number : 58-174850

(71)Applicant : FURUKAWA BATTERY CO LTD:THE  
HONDA MOTOR CO LTD

(22)Date of filing : 21.09.1983


(72)Inventor : NIIMURA KIMIO  
KOGA NORIO  
MOTODATE SHOJI  
SHIGA TOMOKAZU  
KANEKO MASAYA  
SANO ICHIRO  
TSUBUKI AKIHIRO

## (54) SEALING OF STORAGE BATTERY TERMINAL

### (57)Abstract:

**PURPOSE:** To increase shock resistance and vibration resistance by pressing the upper end inner circumference of post inserting through hole of cover plate against outer circumference of terminal of post, and pressing the lower end inner circumference of the post inserting through hole of the cover plate against a periphery step of the post.

**CONSTITUTION:** A post inserting through hole 4 of cover plate 3 is formed in a cone shape and hole diameter of the upper end inner circumference 8b is formed so as to become smaller than diameter of a terminal 5a of post 3. When the terminal 5a is inserted into the through hole 4, an O-ring 6 is compressed between a downward slant middle inner circumference 8a and a flange 7 to form strong sealing. The terminal 5a is pressed against the upper end inner circumference 8b of the cover plate 3, and the post 5 is locked to the lower end inner circumference 8c by a periphery step 7a of the flange 7 to form steady sealing.



## LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the  
examiner's decision of rejection or application  
converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of  
rejection]

[Date of requesting appeal against examiner's decision  
of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office